

FLANGED DIAPHRAGM SEALS

General:

- Standard: Clamped Type Diaphragm with Upper & Lower Housing Gaskets
 Option: Available with Diaphragm Welded to Upper Housing
 (Note: Model Number changes to '200') *
- Instrument Connection: 1/4" or 1/2"NPT *
- Process Connection: ½", ¾", 1" 1 ½" RF Flanged *
- Pressure Rating: per ANSI B16.5 150 # or 300 # Standard *
- Upper Housing: Chrome Plated Carbon Steel Standard Stainless Steel Available *
- Bolting: Grade 8 Galvanized Steel Standard Stainless Steel Available *
- RTJ Connection Also Available

* (Others Available upon Request)

Wetted Materials Available(Includes Diaphragm and Lower Housing):

316 SS, 304 SS, 316L SS, 304L SS, Hastelloy C276, B2, Inconel 600, 625, Tantalum (Diaphragm Only), Nickel, Monel 40, Titanium, Carpenter 20, Teflon, PVC, Kynar, Others upon Request

Gasket Materials:

Buna N, Viton, Teflon, Grafoil, Others upon request

Fill Fluids Available:

Glycerine (standard), Silicone (various Grades and viscosities), Glycol, Halocarbon, Slytherm, Others Upon Request

100-FL-1				Δ
Process Connection		А	В	
1/2"	150 #	3 ½"	1 3/8"	C B B I/2" or 3/4" Flanged Off Line
3/4"		3 ¾"	1 11/16"	
1/2"	300 #	3 ¾"	1 3/8"	
3/4"		4 5/8"	1 11/16"	
	100-	-FL-2		_
Process Connection		А	В	
1"	150 #	4 1⁄4"	1 3/8"	c
1"	300 #	4 7/8"	1 9/16"	1" Flanged Off Line
	100-	-FL-3		A — — A
Process Connection		А	В	c
All Dir	nensions Accord	ling to Size and	Rating.	
				В —
				1 1/2" or Larger Flanged Off Line

