

Sanitary Application Diaphragm Seal

Type C Series

General Information for Type C Series Seals

- ✓ C models are clamp attached.
- ✓ C models are all welded 316L stainless steel construction and are designed to meet 3-A requirements.
- ✓ **CSTG** models are **clamped attached** and supplied with all stainless USG **Model 656** or 659 pressure gauge, designed to meet **3-A** requirements.
- ✓ Ideally suited for Food, Dairy, Beverage, Pharmaceutical, or High Purity applications.
- ✓ Quick connection and disconnection from process, ideal for washdowns, line cleanout/purge, flushing, or changes to process media.
- ✓ Compatible with a variety of piping systems, e.g., Ladish TriClover and Cherry-Burrell. Process connection sizes are 1-1/2", 2", and 3".
- ✓ Clamps <u>are not</u> supplied with seals and are ordered seperately as required.
- ✓ Filling and attachment options are available. If no filling and attachment options are used, enter a dash (" ") for those characters.
- ✓ Special options are available. If no special options are used, enter a dash (" ") for those characters.

Model Selection Guide

Туре	Piping System	Operating Pressure	Volumetric Displacement
CSI	Cherry-Burrell "I" Line CIP	10 PSI & Up	0.06 in ³
	Seal replaces 16 AL Cap	10 PSI & Up	0.06 in ³
CSQ	Cherry-Burrell "Q" Line CIP	10 PSI & Up	0.06 in ³
	Seal replaces 16 AQ Cap	10 PSI & Up	0.06 in ³
CST & CSTG	Ladish TriClover	50 PSI & Up	0.007 in ³
	GC "Fast Clamp"	10 PSI & Up	0.06 in ³
	Cherry-Burrell "S" Clamp	10 PSI & Up	0.06 in ³
	Seal replaces 16A	10 PSI & Up	0.13 in ³





Figure 1: 2" and 1-1/2" CST seals

