Severe Service



SPECIFICATIONS

ACCURACY

± 2.5% of range across full scale

CASE SIZES

40 or 50 mm diameter

CASE MATERIAL

304 Stainless Steel

CASE STYLE CB - Center Back mount

TUBE & SOCKET

Copper Alloy tube with nickel plated brass socket

MOVEMENT

Brass

CONNECTION 1/8 NPT & 1/4 NPT

RANGES

15 to 160 psi

DIAL STANDARD Triple scale psi/BAR/kPa

DIAL COLOR

Black markings on white

POINTER

Aluminum, black painted

WINDOW

Acrylic

FILL MEDIUM Glycerine Standard

RESTRICTOR

Standard, all ranges

VENT PLUG

Filler/pressure relief plug

TEMPERATURE LIMITS

0 - 140° F (filled)

WEIGHT 40mm

0.5 lb.

50_{mm} 0.5 lb.

40MM & 50MM SEVERE SERVICE GAUGE

- Copper Alloy Internals
- · Glycerine Filled
- · Center Back Mount Only

Marsh Instruments Liquid-Filled Gauges are designed to perform in rugged and harsh environmental conditions - especially where pulsation and vibration is a problem. Liquid Filled Gauges offer a significant cushioning and dampening effect, reducing pointer flutter and internal gauge damage. Liquid Filled Gauges feature a ventable top fill plug and can be mounted on a horizontal or vertical plane. The hermetically sealed construction reduces the chance of leaks and makes field filling an easy option.


ար- անրարակականուրույնում արականայում արևութարարարան արևու

Typical applications include refineries, chemical, oil & gas, marine and OEM processes.

STANDARD RANGES & PART NUMBERS

TYPE	40MM & 50MM GAUGES	
Size	40mm	50mm
Case Material	304 Stainless Steel	304 Stainless Steel
Internals	Copper Alloy	Copper Alloy
Mounting / Case Style	СВ	СВ
Connection	% NPT	¼ NPT
Scale Standard	psi/BAR/kPa	psi/BAR/kPa
O to 15 psi	M4040P	M5040P
0 to 30 psi	M4042P	M5042P
0 to 60 psi	M4046P	M5046P
0 to 100 psi	M4048P	M5048P
0 to 160 psi	M4052P	M5052P

40MM AND 50MM GAUGE OPTIONS					
OPTION	TYPE	SUFFIX	AVAILABLE ON MODELS		
Custom Dials	Custom face	M	See Marsh Price List for minimums		
Other Ranges			Consult factory for availability		
Fill Medium	Silicone (SL)	1	Consult factory		



A-Size	В	C	Ε
40mm Dia	27.00mm	11.5mm	13.00mm
	1.06"	0.45"	0.51"
50mm Dia	30.00mm	11.5mm	10.00mm
	1.18"	0.45"	0.39"

ALL DIMENSIONS ARE NOMINAL

