

Type 332.30

Type 332.30 test gauges feature a solid front, blow-out back safety case design and adjustable knife-edge pointers. The mirror bands on the dial assure precise readings and eliminate parallax error. Extremely sensitive and highly accurate, WIKA type 332.30 test gauges are excellent for instrument shops, gauge repair and calibration shops, testing laboratories and other applications demanding high precision and consistent results.



Standard Features

Size:	6"	Pointer:	Black aluminum, adjustable knife-edge
Case:	304 SS, solid-front	Movement:	Stainless steel
Ring:	Polished stainless steel	Accuracy:	±0.25% of span
Wetted Parts:	316L SS	Connection:	ASME B40.100 Grade 3A
Window:	Safety glass		
Dial:	White aluminum, with mirrored band		

Type	332.30
Size	6"
Connection	LM
Conn. Size	1/2" NPT
Press. Scale	PSI
30" Hg	50719092
30"-0-15 psi	
30"-0-30 psi	
30"-0-60 psi	
30"-0-100 psi	
30"-0-160 psi	
30"-0-200 psi	
15 psi	
30 psi	
60 psi	
100 psi	4207408
160 psi	4277416
200 psi	50407848
300 psi	4248946
400 psi	50046128
600 psi	4286112
800 psi	
1,000 psi	50179691
1,500 psi	50046136
2,000 psi	
3,000 psi	4282559
5,000 psi	9744309
10,000 psi	
Accessory order codes (installed)	
Front flange, SS	+ FF
Restrictor	+ R

Available Options

- Front flange, stainless steel
- Rear flange, stainless steel
- Cleaned for oxygen service
- Special connections

Applications

- Calibration and testing laboratories
- Suitable for gaseous or liquid media that will not obstruct the pressure system or corrode stainless steel wetted parts

Abbreviations

LM - Lower mount
SS - Stainless steel

Stock items shown in **blue** print.