

## Type 332.54

WIKA type 332.54 inspector's test gauges are convenient for field calibrations. They have an accuracy of  $\pm 0.25\%$  which meets ASME B40.100 Grade 3A. The mirrored band on the dial and the knife-edge pointer make it easy to take accurate readings from the gauge. Type 332.54 test gauges are supplied standard with a padded, nylon carrying pouch.



### Standard Features

<b>Size:</b>	4"	<b>Pointer:</b>	Black aluminum, adjustable knife-edge
<b>Case:</b>	304 SS	<b>Movement:</b>	Stainless steel
<b>Ring:</b>	Polished stainless steel	<b>Accuracy:</b>	$\pm 0.25\%$ of span (ASME B40.1 Grade 3A) 0/30" Hg to 600 psi and 2,000 psi to 20,000 psi; $\pm 0.5\%$ of span (ASME B40.1 Grade 2A) 600>2,000 psi
<b>Wetted Parts:</b>	316L SS	<b>Connection:</b>	Lower mount
<b>Window:</b>	Safety glass		
<b>Dial:</b>	White aluminum, with mirrored band		

Type	332.54
<b>Size</b>	<b>4"</b>
<b>Connection</b>	LM
<b>Conn. Size</b>	1/4" NPT
<b>Press. Scale</b>	PSI
30" Hg	<b>4220013</b>
30"-0-15 psi	4362336
30"-0-30 psi	4255232
30"-0-60 psi	4333781
30"-0-100 psi	4237961
30"-0-160 psi	4213176
30"-0-200 psi	4200741
15 psi	<b>4220021</b>
30 psi	4220030
60 psi	<b>4220048</b>
100 psi	<b>4220056</b>
160 psi	<b>4220064</b>
200 psi	<b>4220072</b>
300 psi	<b>4220081</b>
400 psi	4220099
600 psi	<b>4220102</b>
800 psi	
1,000 psi	<b>4220111</b>
1,500 psi	4246004
2,000 psi	4249250
3,000 psi	4237979
5,000 psi	4243269
10,000 psi	50044796
Accessory order codes (installed)	
Rear flange, SS	+ RF
Restrictor	+ R

### Available Options

- Special connections
- Instrument glass window
- Cleaned for oxygen service

### Applications

- Inspector's test gauge
- Testing and calibration of other pressure measuring instruments
- Suitable for fluid medium which does not clog port or corrode 316 SS

**Abbreviations**  
LM - Lower mount  
SS - Stainless steel

Stock items shown in blue print.