



REOTEMP All-Angle thermometer allows for easy temperature monitoring from any position.



### Standard Features

- Complete 180° Adjustability
- All Stainless Steel Construction
- Hermetically Sealed (ASME B40.3)
- Accurate to 1% of Full Scale
- Standard External Reset
- Silicone Fillable for Vibration
- 360° Case Rotation

### How to Order

LL

060

1

F43

SF

Models	Stem Length	Connection	Temperature Ranges <small>See pg.13 for a full list.</small>	Options
<b>Standard Models</b>		<b>Standard Threaded</b>	<b>Fahrenheit Ranges</b>	
<b>LL</b> = Model L (3" dial, reset)	<b>025</b> = 2.5"	<b>1</b> = 1/2" NPT (std.)	<b>F23</b> -40 TO 160°F	<b>PS</b> = Pointed Stem
<b>MM</b> = Model M (4" dial, reset)	<b>040</b> = 4"	<b>5</b> = 3/4" NPT adapter	<b>F55*</b> 25 TO 125°F	<b>SF</b> = Silicone Fill (max temp 550°F)
<b>JJ</b> = Model J (5" dial, reset)	<b>060</b> = 6"	<b>U</b> = 1/2" NPT Union	<b>F43</b> 0 TO 200°F	<b>SS</b> = 316 SS Stem
	<b>090</b> = 9"		<b>F47</b> 0 TO 250°F	<b>F3</b> = 3/8" dia. Stem
	<b>120</b> = 12"	<b>Sanitary*</b>	<b>F63</b> 50 TO 300°F	<b>PC</b> = Acrylic Window
	<b>150</b> = 15"	<b>C</b> = 1-1/2" Tri-Clamp	<b>F67</b> 50 TO 500°F	<b>PY</b> = Polycarbonate Window
	<b>180</b> = 18"	<b>L</b> = 2" Tri-Clamp	<b>F81</b> 150 TO 750°F	<b>TG</b> = Tempered Glass Window
	<b>240</b> = 24"	<b>M</b> = 3/4" Tri-Clamp	<b>F85</b> 200 TO 1000°F	<b>MM</b> = Max/Min Pointer
	<b>300</b> = 30"		<b>Celsius Ranges</b>	
	<b>360</b> = 36"		<b>C23</b> -40 TO 70°C	
	-Intermediate lengths available up to 80"		<b>C55*</b> 0 TO 50°C	
	-Specify length in inches + tenths		<b>C43</b> 0 TO 100°C	
			<b>C47</b> -20 TO 120°C	
			<b>C59</b> 0 TO 150°C	
			<b>C67</b> 0 TO 250°C	
			<b>C81</b> 0 TO 400°C	
			<b>C85</b> 100 TO 500°C	
			<b>Dual F/C Ranges</b>	
			<b>D23</b> -40 TO 160°F & -40 TO 70°C	
			<b>D55*</b> 25 TO 125°F & 0 TO 50°C	
			<b>D43</b> 0 TO 200°F & 0 TO 100°C	
			<b>D47</b> 0 TO 250°F & -20 TO 120°C	
			<b>D63</b> 50 TO 300°F & 10 TO 150°C	
			<b>D67</b> 50 TO 500°F & 0 TO 250°C	
			<b>D81</b> 150 TO 750°F & 0 TO 400°C	
			<b>D85</b> 200 TO 1000°F & 100 TO 500°C	
				For Thermowells see pg. 14
		<small>*-Other sizes available</small>	<small>*-Not available in 2.5" stem.</small>	