



Liquid-In-Glass Thermometer

All Angle Industrial



Specifications:

Case: Modern V-shape design with parts molded of GE Valox® polyester, in black textured finish. Heavy glass protected front firmly secured by spring action.

Stem: Tapered bulb chambers are made of precision ground aluminum. The tapered chamber forms a metal contact with matching taper in the sockets assuring maximum speed of response to temperature changes. Graphite is used as a conducting media between bulb chamber and glass tube.

Locking Device: Adjustable case locknut and angle adjusting screw work independently to provide full 360° positioning of thermometer case and stem.

Tube & Capillary: Mercury filled-magnifying lens "Red Reading" tube (Spirit Filled option available). Precision made to guarantee accuracy within 1% of scale range. Silicone shock mounting for lasting durability. When Mercury is not desired, alcohol-based spirit fill is available

Scale: 9" scale with white coated aluminum and permanently baked bold black markings.

Applications: REOTEMP "All Angle" Industrial Thermometers are used in pipelines of all types, commercial building application (heating & cooling), process piping, tanks, boilers, etc.

How to Order

9VX35

016

SOC35B

INDUSTRIAL THERMOMETERS
9" Scale, All Angle with
1 1/4"-18" Swivel Nut

Stem	Part #	
	Mercury Filled	Spirit Filled
3 1/2"	9VX35	9VS35
6"	9VX06	9VS06
9"	9VX09	9VS09

1. Part #
2. Range Code
3. Accessories

Shaded items normally in stock.

RETORT THERMOMETERS



For Rubber Vulcanizers, Retorts, Coolers, Kettles.
9" Scale Straight or Angle Form,
3 1/2" 304 SS Stem, with 3/4" NPT 304 S.S. Hub.

Range	Form	Part #
170/270°F & 0/30psi	Angle	9RA35F
170/270°F & 0/30psi	Straight	9RS35F
80/130°C & 0/2 kg/cm2	Angle	9RA35C
80/130°C & 0/2 kg/cm2	Straight	9RS35C
200/400°F & 0/200psi	Angle	9RA35FV
200/400°F & 0/200psi	Straight	9RS35FV

STANDARD

Code	Range	Divisions
411	-40 TO 110°F	2°
118	-10 TO 180°F	2°
212	-20 TO 120°F	2°
012	0 TO 120°F	1°
016	0 TO 160°F	2°
318	30 TO 180°F	2°
324	30 TO 240°F	2°
330	30 TO 300°F	2°

Separable Sockets 3/4" NPT External

	Stem Length	Insertion Length	Extension Neck Length	Brass	304 SS
	3 1/2" 6" 9"	2 1/2" 5" 8"	- - -	SOC35B SOC06B SOC09B	SOC35S SOC06S SOC09S
	6" 9"	2 1/2" 5 1/2"	2 1/2" 2 1/2"	SEN06B SEN09B	SEN06S SEN09S
Union Hubs					
3/4" NPT External Thread					
				UH3B	UH3S

Master Gauge Co.



WHEN UNDER PRESSURE THINK OF US!

1150 W. GRAND AVE. CHICAGO, IL 60642 - TOLL-FREE: 1-800-259-2705 - PHONE: 1-312-666-2705 - FAX: 1-312-666-6458 - MASTERGAUGECo.COM